



IFAM.E476316
Light-emitting-diode Surface-mounted Luminaires

[Page Bottom](#)

Light-emitting-diode Surface-mounted Luminaires

[See General Information for Light-emitting-diode Surface-mounted Luminaires](#)

BEGHELLI INC
3250 CORPORATE WAY
MIRAMAR, FL 33025 USA

E476316

Light-emitting-diode Luminaires, Surface-Mounted. Dimmable models, Suitable for damp location, Model(s) V2-HO-WT**-120-277V Where WT** refers to the CCT. WT30 = 3000K, WT35 = 3500K, WT40 = 4000K. WT50 = 5000K.

V2-LO-WT**-120-277V Where WT** refers to the CCT. WT30 = 3000K, WT35 = 3500K, WT40 = 4000K. WT50 = 5000K.

V4-HO-WT**-120-277V Where WT** refers to the CCT. WT30 = 3000K, WT35 = 3500K, WT40 = 4000K. WT50 = 5000K.

V4-LO-WT**-120-277V Where WT** refers to the CCT. WT30 = 3000K, WT35 = 3500K, WT40 = 4000K. WT50 = 5000K.

Light-emitting-diode surface-mounted Luminaires, Model(s) SPA-2-HT-20W-WTXX-120-277V (@)

SPA-3-HT-30W-WTXX-120-277V (@)

SPA-4-HT-40W-WTXX-120-277V (@)

[Last Updated](#) on 2016-10-13

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".